

Relay base - ECOR-2-BSC3/4X21



2907521

<https://www.phoenixcontact.com/in/products/2907521>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



ECOR-2 relay base, for industrial relay with 2 or 4 changeover contacts, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

Commercial Data

Item number	2907521
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6313
GTIN	4055626214382
Weight per Piece (including packing)	78.94 g
Weight per Piece (excluding packing)	78.94 g
Customs tariff number	85366990
Country of origin	CN

Relay base - ECOR-2-BSC3/4X21



2907521

<https://www.phoenixcontact.com/in/products/2907521>

Technical Data

Product properties

Product type	Relay socket
--------------	--------------

Electrical properties

Nominal voltage U_N	300 V AC/DC
Nominal current I_N	12 A

Connection data

Input side

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Output side

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section solid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Dimensions

Width	27 mm
Height	78.5 mm
Depth Retaining bracket	86 mm (ECOR-RH-2)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

Relay base - ECOR-2-BSC3/4X21



2907521

<https://www.phoenixcontact.com/in/products/2907521>

Approvals



CSA

Approval ID: 70066743



cUL Recognized

Approval ID: FILE E 113228



UL Recognized

Approval ID: FILE E 113228



EAC

Approval ID: RU C-DE.**08.B.01419

cULus Recognized

Relay base - ECOR-2-BSC3/4X21



2907521

<https://www.phoenixcontact.com/in/products/2907521>

Classifications

ECLASS

ECLASS-9.0	27371603
ECLASS-10.0.1	27371603
ECLASS-11.0	27371603

ETIM

ETIM 8.0	EC001456
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

Relay base - ECOR-2-BSC3/4X21



2907521

<https://www.phoenixcontact.com/in/products/2907521>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Accessories

Relay retaining bracket

Relay retaining bracket - ECOR-RH-2L - 1051972

<https://www.phoenixcontact.com/in/products/1051972>



Relay retaining bracket, with eject function and integrated equipment marking area (8 x 25 mm), to suit relay base ECOR-2, for 29 mm high industrial relay

Relay retaining bracket

Relay retaining bracket - ECOR-RHM-2L - 1047026

<https://www.phoenixcontact.com/in/products/1047026>



Relay retaining bracket, wire model, suitable for ECOR-2... relay base when used with REL-IR-BL... relays

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Plug-in module

Plug-in module - LDP- 12- 24DC - 2833657

<https://www.phoenixcontact.com/in/products/2833657>



Plug-in module, with freewheeling diode and yellow LED, polarity: A1+, A2-, input voltage: 12 ... 24 V DC $\pm 20\%$

Plug-in module

Plug-in module - DP-12-220 DC - 2907517

<https://www.phoenixcontact.com/in/products/2907517>



Plug-in module, with freewheeling diode, polarity: A1+, A2-, input voltage: 12 V DC ... 220 V DC $\pm 20\%$

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Plug-in module

Plug-in module - LV-120-230AC/110DC - 2833738

<https://www.phoenixcontact.com/in/products/2833738>



Plug-in module, with varistor and yellow LED, input voltage: 120 ... 230 V AC / 110 V DC ± 20 %

Plug-in module

Plug-in module - V-120-230UC - 2833880

<https://www.phoenixcontact.com/in/products/2833880>



Plug-in module, with varistor, input voltage: 120 ... 230 V AC/DC ± 20 %

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>



Plug-in module

Plug-in module - RC-120-230UC - 2833767

<https://www.phoenixcontact.com/in/products/2833767>



Plug-in module, with RC element, input voltage: 120 ... 230 V AC/DC ± 20 %

Marker labels

Marker labels - MP 2 - 2833644

<https://www.phoenixcontact.com/in/products/2833644>



Equipment marker, labeling surface 9 x 25 mm

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Wire bridge

Wire bridge - DB 50- 90 BU - 2821180

<https://www.phoenixcontact.com/in/products/2821180>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: blue



Wire bridge

Wire bridge - DB 50- 90 BK - 2820916

<https://www.phoenixcontact.com/in/products/2820916>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: black



Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Wire bridge

Wire bridge - DB 50- 90 GY - 2820929

<https://www.phoenixcontact.com/in/products/2820929>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray



Single relay

Single relay - REL-IR-BL/L- 12DC/4X21 - 1109557

<https://www.phoenixcontact.com/in/products/1109557>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 12 V DC

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Single relay

Single relay - REL-IR-BL- 24DC/4X21 - 1032521

<https://www.phoenixcontact.com/in/products/1032521>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, polarity A1+, A2-, input voltage: 24 V DC

Single relay

Single relay - REL-IR-BL/L- 24DC/4X21 - 1032527

<https://www.phoenixcontact.com/in/products/1032527>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V DC

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Single relay

Single relay - REL-IR-BL/L- 48DC/4X21 - 1109558

<https://www.phoenixcontact.com/in/products/1109558>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 48 V DC

Single relay

Single relay - REL-IR-BL/L-110DC/4X21 - 1109560

<https://www.phoenixcontact.com/in/products/1109560>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 110 V DC

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Single relay

Single relay - REL-IR-BL/L-125DC/4X21 - 1109561

<https://www.phoenixcontact.com/in/products/1109561>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 125 V DC

Single relay

Single relay - REL-IR-BL/L-220DC/4X21 - 1109562

<https://www.phoenixcontact.com/in/products/1109562>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 220 V DC

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Single relay

Single relay - REL-IR-BL/L- 24AC/4X21 - 1109563

<https://www.phoenixcontact.com/in/products/1109563>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V AC

Single relay

Single relay - REL-IR-BL/L-115AC/4X21 - 1109564

<https://www.phoenixcontact.com/in/products/1109564>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 115 V AC

Relay base - ECOR-2-BSC3/4X21

2907521

<https://www.phoenixcontact.com/in/products/2907521>

Single relay

Single relay - REL-IR-BL-230AC/4X21 - 1032529

<https://www.phoenixcontact.com/in/products/1032529>



Plug-in industrial relay in basic design with power contacts, 4 changeover contacts, test key, mechanical switch position indicator, input voltage: 230 V AC

Single relay

Single relay - REL-IR-BL/L-230AC/4X21 - 1032531

<https://www.phoenixcontact.com/in/products/1032531>



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 230 V AC

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in